

Installation Manual

Brand: FK Industries

Product : FK Al-Mg Alloy Rear Lower Link Skids(Pair)|2024+ Toyota Land Cruiser (LC250) 2.4L Turbo Hybrid / 2.7L 4-Cylinder / 2.8L Turbo Diesel

Compatible Vehicle Models: TOYOTA Land Cruiser 250

Product Number: 8119380253

Skid Plate:




- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.



Hardware Kit

Part Diagram	Specification	Qty	Unit
Bolt: 	8mm x 25mm	4	Pcs
Washer: 	8mm x 25mm	4	Pcs
Nut with Handle: 	8mm	4	Pcs
Hardware Kit Part Number:19389553-02			

Tools Required


Tool	Specification	
Socket Wrench	10mm	19mm

- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.



Skid Plate Installation



8x25mm bolts 2 pcs
8x25mm washers 2 pcs
8mm nut with handles 2 pcs

- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.



Safety Precautions

1. Always use jack stands when working under the vehicle. Do not rely solely on a jack.
2. Wear safety gloves and eye protection during installation.
3. Ensure the vehicle is on a flat and stable surface before lifting.
4. Do not overtighten bolts, as this may damage the skid plate or vehicle frame.

Notes & Maintenance

1. Regularly inspect the skid plate for signs of wear or damage, especially after off-road use.
2. Clean the skid plate periodically to remove dirt and debris that may cause corrosion.
3. If any bolts become loose over time, retighten them to the specified torque values.

Torque Specifications for Bolts

Bolt Size	Torque Range (Nm)
M8 Bolts	35-45 Nm
M10 Bolts	70-90 Nm
M12 Bolts	110-130 Nm
M14 Bolts	150-170 Nm
Adjust within the range based on tool accuracy	

- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.

