

Installation Manual


Brand: FK Industries

Product : FK Al-Mg Alloy Rear Lower Link Skids(Pair)|2022+ Ram 1500 TRX 6.2L Supercharged HEMI V8


Compatible Vehicle Models: RAM 1500 TRX

Product Number: 8119492553

Skid Plates:



Brackets:





- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.



Hardware Kit

Part Diagram	Specification	Qty	Unit
Bolt: 	8mm x 25mm	2	pcs
	8mm x 30mm	2	pcs
Countersunk Hex Socket Screw: 	8mm x 18mm	8	pcs
Washer: 	8mm x 25mm	4	pcs
Hardware Kit Part Number:19223054-03			

Tools Required

Name	Specification	
Socket Wrench	10mm	T30

- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China



For technical support or additional product information, please contact our customer service team.

Bracket Installation




8x25mm bolt 1 pc
8x30mm bolt 1 pc
8x25mm washers 2 pcs



Skid Plate Installation



8x16mm countersunk hex socket screws 4 pcs



- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.



Safety Precautions

1. Always use jack stands when working under the vehicle. Do not rely solely on a jack.
2. Wear safety gloves and eye protection during installation.
3. Ensure the vehicle is on a flat and stable surface before lifting.
4. Do not overtighten bolts, as this may damage the skid plate or vehicle frame.

Notes & Maintenance

1. Regularly inspect the skid plate for signs of wear or damage, especially after off-road use.
2. Clean the skid plate periodically to remove dirt and debris that may cause corrosion.
3. If any bolts become loose over time, retighten them to the specified torque values.

Torque Specifications for Bolts

Bolt Size	Torque Range (Nm)
M8 Bolts	35-45 Nm
M10 Bolts	70-90 Nm
M12 Bolts	110-130 Nm
M14 Bolts	150-170 Nm
Adjust within the range based on tool accuracy	

- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.

