

Installation Manual


Brand: FK Industries

Product : Fuken FK Al-Mg Alloy Front Lower Control Arm Skids(Pair)|2012+ NISSAN PATROL Y62 4.0L V6 / 5.6L V8

Compatible Vehicle Models: NISSAN PATROL Y62

Product Number: 8119726251

Skid Plates:





- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.



Hardware Kit

Part Diagram	Specification	Qty	Unit
Carriage Bolt: 	8mm x 80mm	2	pcs
Stainless Steel Socket Head Cap Screw: 	8mm x 40mm	4	pcs
Nut with Handle: 	8mm	2	pcs
Nut: 	8mm	2	pcs
Washer: 	8mm x 25mm	2	pcs
Block-Welded Nut: 	8mm	2	pcs
Hardware Kit Part Number:19726251-02			

Tools Required



Name	Specification
Open-End Wrench	13mm

- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China



For technical support or additional product information, please contact our customer service team.

Skid Plate Installation



8x80mm carriage bolt 1 pcs
8mm nut 1 pcs
8x25mm washer 1 pcs

8x40mm socket head cap screw 1 pcs
8mm block-welded nut 1 pcs

8x40mm socket head cap screw 1 pcs
8mm nut with handle 1 pcs

Safety Precautions

1. Always use jack stands when working under the vehicle. Do not rely solely on a jack.
2. Wear safety gloves and eye protection during installation.
3. Ensure the vehicle is on a flat and stable surface before lifting.
4. Do not overtighten bolts, as this may damage the skid plate or vehicle frame.

Notes & Maintenance

1. Regularly inspect the skid plate for signs of wear or damage, especially after off-road use.
2. Clean the skid plate periodically to remove dirt and debris that may cause corrosion.
3. If any bolts become loose over time, retighten them to the specified torque values.

Torque Specifications for Bolts

Bolt Size	Torque Range (Nm)
M8 Bolts	35-45 Nm
M10 Bolts	70-90 Nm
M12 Bolts	110-130 Nm
M14 Bolts	150-170 Nm
Adjust within the range based on tool accuracy	

- **Website:** shop.fkoffroad.com
- **Email:** support@fkoffroad.com
- **Phone:** +86 177 0115 5098 (Whatsapp available)
- **Address:** No.3 Tongda Road, Dongmaquan Town, Wuqing District, Tianjin, China

For technical support or additional product information, please contact our customer service team.

